





Indigo™ Series 322 Ice Cube Machine

☐ ID-0323W Model: ID-0322A ☐ IY-0324A

Ice Machine Flectric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available)

Minimum circuit ampacity:

Air-cooled: 11.5 1ph Water-cooled: 10.7 1ph

Maximum fuse size:

Air-cooled: 15 amps Water-cooled: 15 amps

Indiao Series i-322

Ice Machine on B-320 Bin

Specifications

BTU Per Hour:

3,300 (average) 4,500 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- **Ambient Temperature Range:** 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

IY-0325W

- Space-Saving Design Up to 350 lbs. (159 kgs.) daily ice production and only 22" (55.88 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- DuraTech™ Exterior provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available **LuminIce™ Growth Inhibitor** controls the growth of bacteria and yeast within the foodzone.



Ice Shape





Dice ⁷/8" X (2.22 x 2.22 x 2.22 cm)













: ISO 9001:2008 :

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







i-322 on B-320 Storage Bin 24.50" (62.23 cm) (A) Electrical Entrance (2) Options B 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) © 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units) 1/2" (1.27 cm) Auxillary Base Drain Socket (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain (G) 3/4" (1.91 cm) Bin Drain 32 00' (81.30 cm) **Installation Note** 34.00" (86.30 cm) Minimum installation clearance: 22".00 (55.88 cm) Top/sides: 8" (20.32 cm): Back is 5" (12.7 cm)

Space-Saving Designs



	B-320	B-420
Height	59.50" 151.13 cm	71.50" 194.31 cm
Width	22.00" 55.88 cm	22.00" 55.88 cm
Depth	34.00" 86.30 cm	34.00" 86.30 cm
Bin Storage	210 lbs. 95 kgs.	310 lbs. 141 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

Specifications

			1	Ice Production	on 24 Hours	Power Usage kWh/100 lbs.	Water Usage/100 lbs. 45.4 kgs. of Ice	ENERGY
		Model	Ice Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	@90°Air/70°F	Potable Water	STAR*
	AIR-COOLED	ID-0322A	dice	335 lbs.	225 lbs.	7.49	23.9 Gal.	
		ID-0322A		152 kgs.	102 kgs.	7.49	90.5 L	*
		IY-0324A half-dice	half-dice	350 lbs.	230 lbs.	7.32	23.9 Gal.	*
			-	159 kgs.	104 kgs.		90.5 L	
	WATER-COOLED	ID-0323W d	dice	330 lbs.	270 lbs.	6.19	23.9 Gal.	NA
		ID-0323VV		150 kgs.	122 kgs.	0.19	90.5 L	INA
		IY-0325W half-dice	350 lbs.	290 lbs.	5.94	23.9 Gal.	NA	
				159 kgs.	132 kgs.	5.94	90.5 L	INA
	Ž		* Water-	ter-cooled Condenser Water Usage / 100 lbs /45 4 kgs Of Ice: 193 gal/731 l				

* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 193 gal/731 L.

* Water-cooled models are excluded from ENERGY STAR qualification.

Order ice storage bin separately.

Accessories

LuminIce™ Growth Inhibitor reduces yeast and bacteria growth for a cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



Arctic Pure®
Water Filters
Reduces

Reduces sediment and chlorine odors for better tasting ice.



AuCS® schedules and performs routine ice machine cleaning automatically.



4775 (replaces 2980D S-322) ©2011 Manitowoc 1/11 Continuing product improvement may necessitate change of specifications without notice.

2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com



