

Model 736

COMPACT COUNTERTOP HEAT
TREATMENT SOFT SERVE FREEZER

LESS DOWNTIME
MORE
THROUGHPUT

Great performance in a smaller
footprint to meet demands of
your busiest dayparts.

FEATURES

- **Smaller footprint** optimizes valuable space
- **Effective heat treatment** provides consistent taste and structure
- **Gear pump technology** easily controls overrun to your given needs
- **Heat treatment system** provides labor savings
- **Recovers quickly** for high volume throughput
- **Versatility** to create a variety of new products



Smaller Footprint



Heat Treatment System



Gear Pump

Introducing our newest addition to the Taylor® frozen dessert product line—the **Model 736 compact countertop heat treatment soft serve freezer**. Combining a proven heat treatment system with a smaller footprint, the Model 736 is ideal for operations that are high on demand and low on space.

WITH THE TAYLOR MODEL 736, LESS IS DEFINITELY MORE!

Smaller Footprint

At just 400mm (<16 inches) wide, the Model 736 may be small, but it is mighty, with high volume throughput. A streamlined, compact design and side condenser make it ideal for back counter installation anywhere space is limited.

Heat Treatment System

The Model 736 features a daily heating and cooling cycle to help you save on labor costs and reduce product waste. How? It safely maintains dairy products up to two weeks before a complete disassembly and cleaning is required.

Gear Pump

Get the perfect ratio of mix to air every time for improved texture and product consistency, with the gear pump technology used in the Model 736. It features an easily adjustable manual overrun feature, and with less parts, it's easy to assemble and disassemble.

MODEL 736 SPECIFICATIONS AND CAPACITY

Width	15-3/4"	400mm	
Depth	30-7/16"	773mm	
Height	35-3/4"	908mm	
<i>Mounted on standard feet h. 4" (100mm)</i>			
Weight			
Net	273.4lb	124kg	
Crated	339.5lb	154kg	
Beater Motor	One, 2 HP (1500 W)		
Freezing Cylinder	One, 2.1 quart (2 liter)		
Mix Hopper	One, 8.5 quart (8 liter)		
Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	kW
380-415/50/3	10A	5.5	2.6
One dedicated electrical connection is required. Manufactured to be permanently connected. For exact electrical information, always refer to the data label of the unit.			
Air cooled.			

DISTRIBUTOR INFORMATION



750 North Blackhawk Blvd.
 Rockton, IL 61072
TF 800.255.0626 **PH** 815.624.8333
FX 815.624.8000
 www.taylor-company.com
 info@taylor-company.com