



Item No. _____

R160

Frozen Food Dispenser

R160



Fryer Baskets Sold Separately

Features



Dispenses and stores frozen fries directly into fryer basket. Ensuring that the fries are cooked from frozen, results in improved product quality, consistency and yield. Unit is designed for simple daily cleaning of cabinet and refrigeration filter. Provides storage of up to two baskets, flexible store configuration for left or right hand door opening. Self contained environmentally friendly refrigeration system using R290 with cold wall construction.

Dispensing

Push button dispensing system enables the operator to fill one basket and slide another basket back into the fill position.

Operation

Operation of the R160 Frozen Food Dispenser is easily controlled by a power switch, simple visual portion control and an ergonomic basket fill location.



Weights	lbs.	kgs.
Net	257	117
Crated	289	131

	lbs.	kgs.
Hopper Capacity	36	16.3

Dimensions	in.	cm.
Width	16.5	42
Depth	28	71
Height	67.75	173

Electrical	Total Amps	Poles (P) Wires (W)
115/60/1 Air	8.0	5-15P
220-240/50/60/1 Air	4.6	---

Power Cord Length	8 ft.	2.43 m
-------------------	-------	--------

This unit may be manufactured in other electrical characteristics and may have additional regulatory agency approvals. Consult the local Taylor distributor for other electrical characteristics and agency approvals based on specific electrical and country requirements.

(For exact electrical information, approval marks and refrigerant, always refer to the data label of the unit.)

Continuing research results in steady improvements; therefore, these specifications are subject to change without notice.

Bidding Specs

Electrical: Volt _____ Hz _____ ph _____
 Neutral: Yes No Cooling: Air Water NA

Options: _____

All options may not be available in combination with others or with all electrical or cooling configurations. Please consult your local Taylor distributor.

Authorized Taylor Distributor

Specifications

Electrical

One dedicated electrical connection is required. See the Electrical chart for the proper electrical requirements. Manufactured to be cord connected. Consult your local Taylor distributor for cord & receptacle specifications as local codes allow.

Refrigeration System

One, R290

Note: Consult local Taylor distributor for refrigerant configurations.

Air-Cooled

Minimum 4 in. (101.6 mm) rear, and 2 in. (508 mm) side clearance. Minimum air clearances must be met to ensure adequate airflow for optimum performance.

Accessories

- Side-Mount 4 Fryer Basket Rack
- Fryer Basket



750 N. Blackhawk Blvd.
 Rockton, Illinois 61072
www.taylor-company.com