Daily Cleaning for the G5[™] Oven

Daily Cleaning

The following steps will help maintain your oven. Use only TurboChef Oven Cleaner and Oven Guard. The use of any other cleaning products can damage critical oven components, resulting in a non-warranty service call.



Step 1: Prepare the Oven

- MARNING: Oven operates at approximately 500°F (260°C) and may cause injury if not allowed to cool properly.
- Turn off the oven by pressing the On/Off key.
- Slightly open the oven door. Cooling takes approximately 40 minutes.
- DO NOT clean the oven until the oven displays \oslash "OVEN OFF".



Step 2: Remove, Clean the Oven Racks

- MARNING: Be sure the oven interior is cool before you remove the oven racks.
- Wash, rinse, and sanitize the oven racks.



Supplies and Equipment

disposable gloves, protective eyewear, dust mask (optional)

Step 4: Clean the Lower Tray

TurboChef Oven Cleaner (Product Number: 103180), TurboChef Oven Guard

(Product Number: 103181), nylon scrub pad, cleaning towel, disposable sani-wipes,

 Remove the lower tray to remove large particles and clean with a damp towel.



Step 5: Apply TurboChef Oven Guard

- Spray TurboChef Oven Guard onto a clean towel. Wipe the oven's interior walls and the inside of the oven door.
- A CAUTION: DO NOT spray Oven Guard directly into the cavity, as it may settle and build up on the heater elements or the convection fan blade, resulting in a non-warranty service call.



Step 3: Clean the Oven Interior

- Use a vacuum hose, clean damp towel, or disposable sani-wipes to remove large particles.
- Spray TurboChef Oven Cleaner onto stains/debris build up and allow it to penetrate stains for five minutes.
- A CAUTION: DO NOT spray Oven Cleaner directly into the cavity, as it may settle and build up on the heater elements or convection fan blade. (see figure 3a)
- Scrub stains with a nylon scrub pad (see figure 3b).
- or disposable sani-wipe to collect any remaining cleaner residue. (see figure 3c).
- Thoroughly dry the cavity and door with a clean dry towel or disposable sani-wipe.



Step 6: Reinstall the Oven Racks

• Be sure to install the oven racks in the same positions they were in before being removed.



Step 7: Clean the Oven Exterior


- Wipe the oven exterior with a clean, damp towel.
- A CAUTION: DO NOT spray chemicals into any openings, such as the louvers on the back panel or the rear filter. Doing so can damage critical oven components, resulting in a non-warranty service call.





Step 8: Check the Rear Filter

- · Remove the filter and rinse it gently in water. If the filter is damaged, replace it using part number i5-9039
- The oven is ready to turn on.



- Wipe the oven cavity and door with a damp towel

